


# DESIGN FEATURES OF HOT BLAST VALVES


- O Increased process heat retention with improved thermal insulation system (thermo blocker) in body and bonnet
- Special design of cooling system to provide optimum flow reduces water heat loading & process heat loss
- O Possible sealing in both directions, floating plate design
- Valve actuation in accordance with customer's requirements (man./electr./ hydr./pneum.)
- O Pressure rating up to 6.0 bar
- O Service temperatures up to 1550 °C
- O Nominal sizes up to DN 2200
- Other sizes or operating conditions on request

#### DESIGN ADVANTAGES

- Optimized cooling system reduces water requirements
- O Improved thermal insulation system reduces thermal stress and extends the total life cycle
- Exchangeable body seats makes maintenance easier & faster
- Decreased heat losses reduce operating/fuel costs & carbon footprint







#### **IRON & STEEL PRODUCT RANGE**

GOGGLE VALVES



GUIDE LEVER VALVES



DOUBLE ECCENTRIC VALVES



**EQUALIZING & RELIEF VALVES** 





DUST DISCHARGE VALVES



BLEEDER VALVES



TUYERE STOCKS (ENERGY SAVING)



WEDGE GATE VALVES

## **ADDITIONAL PRODUCTS**

SNORT VALVES | BACK DRAFT VALVES | BUTTERFLY & LOUVER VALVES NON RETURN VALVES | LINE BLINDS

### **ADDITIONAL SERVICES**

REPAIR SERVICE | REFURBISHMENT & MODIFICATIONS, SPARE PARTS FOR EACH KIND AND BRAND OF VALVES

Valve
Competence
Luxembourg

A COMPANY OF www.sab.lu

Zone Industrielle "Am Potaschberg" 19, op der Ahlkërrech L-6776 Grevenmacher T +352 27 68 54 - 0 | info@vcl.lu www.vcl.lu